EAST Search History

EAST Search History (Prior Art)

Ref Hi #	ts	Search Query	DBs	Default Operator	Plurals	Time Stamp
L2 51	3	(motor near5 (supporting or mounting) near5 plate) and (motor near5 (recess or depress\$4 or cavity or seat or groove or channel or opening or port or aperture or orifice or slot or hole)) and (plate near5 (peg or stub or prong or rib or ridge or finger or pin or rod or rib or dowel or projection or protrusion or post)) and (motor near2 electric) and ((recess or depress\$4 or cavity or seat or groove or channel or opening or port or aperture or orifice or slot or hole) near5 (peg or stub or prong or rib or ridge or finger or pin or rod or rib or dowel or projection or protrusion or post)) and ((recess or depress \$4 or cavity or seat or groove or channel or opening or port or aperture or orifice or slot or hole or peg or stub or prong or rib or ridge or finger or pin or rod or rib or dowel or projection or protrusion or post)) 4444444444444444	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	OR	ON	19:56

L7	178	((motor near2 electric) same ((aligning or alignment or positioning or locator or locating or orientation) near1 (boss\$4 or peg or stub or prong or rib or ridge or finger or pin or rod or rib or dowel or projection or protrusion or post)) and ((boss\$4 or peg or stub or prong or rib or ridge or finger or pin or rod or rib or dowel or projection or protrusion or post) or ridge or finger or pin or rod or rib or dowel or projection or post) near5 (angl\$4 or inclin \$4 or slant\$4 or oblique or bevel\$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/09/21 21:05
		oblique or bevel\$4 or chamfer cant\$4))				

9/21/09 9:06:46 PM